

Features

- Quick disconnect connectors, no tools required for sensor connection.
- Water-tight mini sure-seal® connectors.
- Very high temperature shielded cable.

Description


Sensor cable connects four sensors. Inputs are identified with yellow labels: B1, B2, B3, B4. Also available with C labels.

Specifications

- Connectors operating temp.: -40°C to 105°C.
- Weight: 82grams (2.892oz).
- 11.25" [285 mm] total length

Installation

- Carefully align indexing rib when mating mini sure-seal® connectors.
- Do not bend cables with curvature radius smaller than 1.60" [40 mm].
- Do not place cables near sources of interferences, such as ignition coils, plug leads, electronic modules or antennas.
- Verify that cables are not trapped or stretched by surrounding moving parts.



Cable and Connector pin-out		
3 conductors cable color	DD15M10JVLX PIN #	Signal description
White	1	Signal 1
White	2	Signal 2
White	3	Signal 3
White	4	Signal 4
Shield	5	Shield Signal 1
White/Orange	6	V+ Signal 1
White/Orange	7	V+ Signal 2
White/Orange	8	V+ Signal 3
White/Orange	9	V+ Signal 4
Shield	10	Shield Signal 2
White/Blue	11	Ground Signal 1
White/Blue	12	Ground Signal 2
White/Blue	13	Ground Signal 3
White/Blue	14	Ground Signal 4
Shield	15	Shield Signal 3 – Shield Signal 4